

WATER & WASTE WATER



WATER & WASTE WATER

Why Solcon?

Solcon Soft Starters provide solutions for the most demanding applications in the Water and Waste Water industry. As one of the first companies to penetrate the water and waste water market, Solcon supplied many municipalities with Soft Starters utilizing Pump Control software. With Solcon's unique algorithm these Soft Starters allow for a choice of unique starting and stopping curves, eliminating the water surge and "Hammer Effect" which may cause pipe damage in water systems. Today, Solcon successfully services the water/wastewater industry worldwide with products known for their long term reliability and robust design, ensuring excellent performance in the harshest environments.



Typical Applications

- Water pumps
- Sewage pumps
- Vertical hollow shaft pumps
- Submersible pumps
- Starting from limited power sources like diesel generators

Special Functions for water pumping application:

- Reduced inrush current & mechanical shock
- Smooth, step-less acceleration & deceleration
- Unique soft starting and stopping characteristics
- Heavy duty, fully rated design
- Sophisticated motor protection package
- Ease of installation and operation
- Preparation for harsh environmental conditions
- Prevention of over pressure & water hammer

Booster Pumps - Medium Voltage



Sewage Pumps - Waste Water treatment Plant

Solcon Product lines for water pumping applications:

- Up to 1000HP (630KW) Low voltage standard duty Soft Starter - **RVS-DX**
- Up to 3000HP (3MW) Low voltage Heavy duty Soft Starter - **RVS-DN**
- Up to 50,000HP (50MW) Medium voltage special design Soft Starter - **HRVS-DN**

How can you protect water systems with Solcon Soft Starters?

Start Curves

Solcon's Soft Starters incorporate an Intelligent Pump Control algorithm that offers selection between five special dynamic voltage ramp-up curves, and Torque or Current curves. Reduces peak torque, while extending acceleration time.



Water Pumps - Valparaiso, Chile



Stop Curves

When pumping to a higher elevation and when the motor is stopped, motor torque may quickly fall below load torque causing abrupt stalling instead of smoothly decreasing speed to zero. This may create a Water Hammer phenomenon resulting in a loud noise, disturbances and damage to the piping network. The Solcon Pump Control enables selection between four dynamic voltage ramp-down or soft stop Torque curves to prevent a stall condition and eliminate Water Hammer.

Final Torque

Prior to the end of the deceleration process, motor torque reaches a level where the load torque is higher than the motor's torque and the valve closes. The motor continues to run against a closed valve (no load) until it stops. Solcon's Final Torque feature enables setting a point where the motor stops when the valve closes, thereby preventing operation without water.



SOLCON

WATER

OIL & GAS

INDUSTRY

MINING

MARINE



Soft Starters ■ Motor Protection ■ Power Controllers

T: +1 724.473.1301 | F: +1 724.473.9506 | E: sales@solconusa.com | W: www.solconusa.com

250 West Kensinger Drive, #300, Cranberry Township, PA 16066 USA